

JUN 02 2006

PATENT
Atty. Dkt. No. WEAT/0023.C2**IN THE CLAIMS:**

Please cancel claim 31 and amend the claims as follows:

1 – 20. (Cancelled)

21. (Currently Amended) A method of sealing an annular area in a wellbore, comprising:

providing a tubular member; and

deforming the tubular member in a manner whereby an outer surface of the tubular member assumes a shape of a non circular ~~-uniform~~ surrounding surface and forms a seal therebetween.

22. (Previously Presented) The method of claim 21, wherein a ductile material disposed on the outer surface of the tubular member forms the seal after deforming the tubular member.

23. (Previously Presented) The method of claim 21, wherein a ductile metal disposed on the outer surface of the tubular member forms the seal after deforming the tubular member.

24. (Previously Presented) The method of claim 21, wherein an elastomer disposed on the outer surface of the tubular member forms the seal after deforming the tubular member.

25. (Currently Amended) A method of forming a profile in a section of tubing within a wellbore, comprising:

providing an expander device having at least one radially extendable expander member, wherein the expander member is extended by application of fluid pressure;

positioning the expander device in the wellbore at a predetermined location in the section of tubing; and

Page 2

460588_1

PATENT
Atty. Dkt. No. WEAT/0023.C2

extending the member to deform the tubing at said location to create the profile in
[[the]] an internal face of the tubing.

26. (Previously Presented) The method of claim 25, wherein the profile is in the form of at least one annular recess.

27. (Previously Presented) The method of claim 25, wherein the tubing is deformed by rolling expansion, the expander member being rotated within the tubing with a face in rolling contact with an internal face of the tubing.

28. (Previously Presented) The method of claim 25, wherein the tubing is deformed by compressive plastic deformation, producing a localised reduction in wall thickness and a subsequent increase in tubing diameter.

29. (Previously Presented) The method of claim 25, wherein the tubing is deformed by compressive plastic deformation, producing flow of wall material to create the profile.

30. (Previously Presented) The method of claim 25, wherein the expander member is in the form of a roller.

31. (Cancelled)

32. (Previously Presented) The method of claim 25, wherein a plurality of radially extendable expander members are provided.

33. (Previously Presented) The method of claim 25, wherein the expander is rotated to create the profile.

Please add the following new claims:

Page 3

460588_1

34. (New) The method of claim 21, wherein deforming the tubular member comprises:
providing an expander member having at least one radially extendable member,
wherein the expander member is extended by application of fluid pressure.
35. (New) The method of claim 21, further comprising positioning a second tubular member in the deformed tubular member.
36. (New) A method of sealing an annular area in a bore comprising:
running a tubular member into the bore; and
deforming the tubular member in a manner whereby an outer surface of the tubular member assumes a shape of an unlined section of the bore and forms a seal therebetween.
37. (New) The method of claim 36, wherein deforming the tubular member comprises:
providing an expander member having at least one radially extendable member,
wherein the expander member is extended by application of fluid pressure.
38. (New) The method of claim 36, wherein a ductile material disposed on the outer surface of the tubular member forms the seal after deforming the tubular member.
39. (New) The method of claim 36, further comprising positioning a second tubular member in the deformed tubular member.